

Via Caduti della Liberazione, 57 21040 Uboldo (VA) – Italia Tel: +39 02 964121 Fax: +39 02 96412294

Web: www.eurocel.it

# PRODUCT INFORMATION EUROCEL 729 GDA

## **DESCRIPTION**

Double sided adhesive tape.

### **PRODUCT DATA**

| Backing  | PET fabric                            |  |
|----------|---------------------------------------|--|
| Adhesive | Synthetic rubber and resins; white    |  |
| Liner    | Double sided siliconized paper; brown |  |

|                                 | Unit   | Value             | Method   |
|---------------------------------|--------|-------------------|----------|
| Total thickness (without Liner) | mm     | 0.155             | PSTC 133 |
| Adhesion to steel               | N/25mm | Int: 20 – Ext: 25 | PSTC 101 |
| Tensile strength MD             | N/25mm | 67                | PSTC 131 |
| Elongation at break             | %      | 10                | PSTC 131 |
| Temp. Resistance                | °C     | 60°C              | =        |

### **APPLICATION**

Double sided carpet tape, given its good tack and adhesion, it offers a valid solution for several kinds of flooring. Thinner version of Eurocel 730 GDA. Not resistant to plasticizers.

| Features                             | Benefits  |  |  |  |
|--------------------------------------|---|--|--|--|
| Synthetic rubber and resins adhesive | <ul> <li>✓ Good tack</li> <li>✓ High adhesion on several surfaces</li> <li>✓ Suitable for most kind of carpets</li> </ul> |  |  |  |
| PET fabric backing                   | <ul> <li>✓ Highly adaptable to various shapes</li> <li>✓ Hand tearable</li> </ul>   |  |  |  |

#### **CONDITIONS OF USE AND CONFORMITY**

Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperature are lower than suggested, it is always required to recondition the tape at normal temperature before use. This information is given to the best of Sicad's knowledge. Values are typical and do not constitute a specification. Customers are required to do their own testing under their working condition for their intended application. Any liability arising in respect of our products will be limited to the value of those products charged to the customer excluding any consequential loss.